

DATA SHEET

Technical Specifications:	
Frequency	13.56 MHz, 125 kHz and magnetic stripe
Certifications	FCC certification
	UL 294 listed
	CE mark
	IC certification
	R&TTE directive
	IP65
Voltage Range	5-16 VDC
Power Supply	Linear DC
System Interfaces	Wiegand / Clock & Data / RS-485
Operating Temperature	-31° F to 151° F
Dimensions	4.43" x 5.17" x 1.15"
Weight	8.9 oz
Technologies Supported	Magnetic stripe (tracks 1, 2, or 3)
	Schlage Proximity
	XceedID® Proximity
	HID® Proximity
	GE/CASI ProxLite®
	AWID® Proximity
	LenelProx®
	Schlage MIFARE®
	XceedID MIFARE®
	aptiQmobile
	aptiQ smart cards using MIFARE®
	aptiQ smart cards using MIFARE® DESFire™ EV1
	DESFire® CSN
	HID iClass® CSN
	Inside Contactless PicoTag® CSN
	ST Microelectronics® CSN
	Texas Instruments Tag-It® CSN
	Phillips I-Code® CSN
Maximum Read Range	Proximity: up to 5"
	MIFARE: up to 4"
	DESFire EV1: up to 2"
	PIV credential: up to 2.5"
Color Options	Black (standard), cream, cool tone gray and warm tone brown

BAC025001

BadgePass Wall Mount Mag Stripe & Keypad Combo Reader (Multi-Tech)



BadgePass Multi-technology Magnetic Stripe Readers are designed to simplify your access control solution. Transition your system from existing magnetic stripe cards to more secure smart card technology at your own pace. Add pin access for dual authentication to your most secure entry points. Versatile and easy to install, BadgePass readers are a great fit for organizations of all sizes.